

0.7 to 10GHz Drop in Isolator

Application

- RF power amplifier protection.
- Digital, Satellite, Mobile Communication.
- Medical, Communication, Security.
- Military, Space and Commercial applications.


RF Characteristics

Part Number	Frequency Range (MHz)	Isolation Min(dB)	VSWR Max	Insertion Loss Max(dB)	Connector Type	Temp.(°C)
5o0112190703748	703 ~ 748	18	1.4	0.7	TAB	-40 ~ +85
5o0112190758803	758 ~ 803	18	1.4	0.6	TAB	-40 ~ +85
5o0112190791862	791 ~ 862	16	1.4	0.7	TAB	-40 ~ +85
5o0112190824894	824 ~ 894	18	1.3	0.55	TAB	-40 ~ +85
5o0112190880960	880 ~ 960	18	1.3	0.5	TAB	-40 ~ +85
5o01121909901130	990 ~ 1130	15	1.5	0.7	TAB	-40 ~ +85
5o011219012301350	1230 ~ 1350	18	1.3	0.4	TAB	-40 ~ +85
5o011219013301390	1330 ~ 1390	20	1.25	0.4	TAB	-40 ~ +85
5o011219014271517	1427 ~ 1517	20	1.25	0.4	TAB	-40 ~ +85
5o011219015651585	1565 ~ 1585	23	1.2	0.3	TAB	-40 ~ +85
5o011219016161620	1616 ~ 1620	23	1.2	0.3	TAB	-40 ~ +85
5o011219017101785	1710 ~ 1785	23	1.2	0.3	TAB	-40 ~ +85
5o011219018052170	1805 ~ 2170	18	1.3	0.5	TAB	-40 ~ +85
5o011219018051880	1805 ~ 1880	23	1.2	0.3	TAB	-40 ~ +85
5o011219019201990	1920 ~ 1990	23	1.2	0.3	TAB	-40 ~ +85
5o011219021102170	2110 ~ 2170	23	1.2	0.3	TAB	-40 ~ +85
5o011219023002500	2300 ~ 2500	23	1.2	0.3	TAB	-40 ~ +85
5o011219024002600	2400 ~ 2600	23	1.2	0.3	TAB	-40 ~ +85
5o011219024962690	2496 ~ 2690	23	1.2	0.3	TAB	-40 ~ +85
5o011219025002700	2500 ~ 2700	23	1.2	0.3	TAB	-40 ~ +85
5o011219027003100	2700 ~ 3100	21	1.2	0.4	TAB	-40 ~ +85
5o011219029003300	2900 ~ 3300	20	1.25	0.4	TAB	-40 ~ +85
5o011219031003600	3100 ~ 3600	20	1.25	0.4	TAB	-40 ~ +85
5o011219033003600	3300 ~ 3600	23	1.2	0.3	TAB	-40 ~ +85
5o011219037004000	3700 ~ 4000	23	1.2	0.3	TAB	-40 ~ +85
5o011219042004400	4200 ~ 4400	21	1.2	0.3	TAB	-40 ~ +85
5o011219044005000	4400 ~ 5000	20	1.25	0.4	TAB	-40 ~ +85
5o011219048005000	4800 ~ 5000	23	1.2	0.3	TAB	-40 ~ +85
5o011219050005500	5000 ~ 5500	23	1.2	0.3	TAB	-40 ~ +85
5o011219050006000	5000 ~ 6000	18	1.3	0.5	TAB	-40 ~ +85
5o011219057005900	5700 ~ 5900	23	1.2	0.3	TAB	-40 ~ +85

Basic Specifications

Size (mm)	12.7*19.1*8
Forward Power(W)	100W
Reverse Power(W)	100W
Connector Type	TAB
Storage temperature	-40°C~+125°C
Impedance	50Ω

Overall dimensions(mm)



Instructions

Tolerances: ±2% unless otherwise stated.

- ◆ It can be dual junction or multiple for high isolation.
- ◆ Only some common frequencies in the table can be produced according to the user's requirements.
- ◆ It supports a one-year standard warranty.